

DELTA COOLING TOWERS P. LTD.

Technical DataSheet - Series DFC60 UX

Model No.	Length (mm)	Width (mm)	Height (mm)	Fan Dia (mm)	Motor (HP)	Rated Power (HP)	Motor RPM	DryWeight (Kg)	Operating Weight (Kg)
6070 UX	2450	1840	3450	1120	3.0	2.55	960	528	1440
6080 UX	2450	2150	3550	1440	5.0	4.43	960	616	1680
6100 UX	2750	2450	3550	1440	7.5	5.54	960	792	2160
6115 UX	3070	2450	3550	1440	7.5	5.75	960	880	2400
6130 UX	3070	2750	3550	1725	7.5	6.05	720	990	2700
6140 UX	3070	3070	3550	1725	7.5	6.28	720	1100	3000
6160 UX	3380	3070	3550	1725	7.5	6.56	720	1210	3300
6170 UX	3680	3070	3550	1725	10.0	8.25	720	1320	3600
6180 UX	3680	3370	3550	1725	10.0	8.45	720	1452	3960
6200 UX	3680	3680	3650	2075	10.0	8.74	600	1584	4320
6220 UX	3980	3680	3650	2075	10.0	8.85	600	1716	4680
6240 UX	4900	3070	3650	2 X 1440	2X7.5	11.51	960	1760	4800
6260 UX	5510	3070	3650	2 X 1725	2X7.5	11.80	720	1980	5400
6280 UX	5510	3380	3650	2 X 1725	2X7.5	12.24	720	2178	5940
6300 UX	5510	3680	3650	2 X 1725	2X7.5	12.69	720	2376	6480
6330 UX	5510	3980	3650	2 X 1725	2X7.5	13.13	720	2574	7020
6360 UX	5510	4300	3650	2 X 1725	2X10.0	16.29	720	2772	7560
6400 UX	6130	4300	3800	2 X 2075	2X10.0	16.70	600	3080	8400
6450 UX	6130	4900	3800	4 X 1440	4X7.5	23.01	960	3520	11400
6500 UX	6130	5510	3800	4 X 1440	4X7.5	24.49	960	3960	10800
6600 UX	6130	6430	3800	4 X 1725	4X7.5	24.78	720	4620	14400
6700 UX	7350	6430	3800	4 X 2075	4X10.0	31.38	600	5544	15120
6800 UX	8570	6130	3800	4 X 2075	4X10.0	33.79	600	6160	16800
6900 UX	9200	6130	3800	6 X 1725	6X7.5	36.73	720	6600	18000
61K0 UX	11020	6130	3800	6 X 1725	6X10.0	48.28	720	7920	21600
61K1 UX	11020	6430	4150	6 X 2075	6X10.0	50.09	600	8316	22680
61K2 UX	13510	6130	4150	8 X 1725	8X7.5	51.33	720	9680	26400
61K3 UX	13510	6430	4150	8 X 1725	8X7.5	51.92	720	10164	27720
61K4 UX	14730	6430	4150	8 X 2075	8X10	62.76	600	11088	30240
61K5 UX	15950	6430	4150	8 X 2075	8X10	65.98	600	12012	32760
61K6 UX	17180	6430	4150	8 X 2075	8X10	68.39	600	12936	35280
61K8 UX	19610	6430	4150	8 X 2300	8X12.5	79.82	500	14784	40320
62K0 UX	22050	6430	4150	8 X 2300	8X12.5	84.81	500	16632	45360
62K2 UX	24530	5820	4650	16 X 1725	16 X 7.5	94.00	720	16720	45600
62K3 UX	24530	6130	4650	16 X 1725	16 X 7.5	99.00	720	17600	48000
62K4 UX	25750	6130	4650	12 X 2100	12X10	103.00	600	18480	50400
62K5 UX	27580	5820	4650	18 X 1725	18 X 7.5	112.00	720	18810	51300
62K6 UX	27580	6130	4650	18 X 1725	18 X 7.5	120.00	720	19800	54000
62K7 UX	27580	6430	4650	12 X 2300	12 X 12.5	125.00	600	20790	56700
62K8 UX	29490	6130	4650	16 X 2100	16 X 10	129.00	600	21120	57600
63K0 UX	25760	7670	4650	12 X 2400	12 X 12.5	132.00	500	23100	63000