





ALL PERIPHERAL ISA (ANGLES) SHALL BE FACED OUTSIDE .

10 mm. HOLES AT THE DISTANCE OF 125mm. ON THE PERIPHERAL OF ISA OF THE BASE FRAME SHALL BE PROVIDED BY FURCHASER.

BOLT / TORR 12mmX150mm LONG.

700

DETAIL-Z

ELEVATION OF PILLER WITHOUT BOLT OF MKD - "S" (QTY-1 NO.)

700

## Notes:-

- All dimensions are in milimeters.
- 3. Makeup and quickfill connection shall be provided with thread connections as per is-544-1955 2. Cooling tower will be assembled on ISA-50x50x6 frame fixed on RCC pillar the frame is under purchasers scope unless othervise stated.
- 4. Inlet & outlet connection shall be provided without flange.
- 5 RCC basin and RCC pillers 250x250x700 ht. And Ø12 x 150 long bolts/tor are under purchaser scope.
- 6. 10 mm hole at the distance of 125mm on the peripheral of ISA of the base frame shall be provided by purchaser.
- Location of outlet connection will be as per the site requirement.
- \$\psi 12x150 long bolts/tor shall be grouted in the centre of outer columns as shown in the drawing.
- All pictures shown are for illustration purpose only and may differ from the actual cooling tower model

	OPERATING WEIGHT (KG.)	FAN DIA AND NOS.	WIDTH OF COOLING TOWER	LENGTH OF COOLING TOWER	MAKEUP AND QUICKFILL CONNECTION	DRAIN & OVERFLOW CONNECTION	OUTLET PIPE CONNECTION	INLET PIPE CONNECTION	DESCRIPTION	2820   2820   3070   3070   470	
		P	Ŧ	E	D	C	В	A	MARK	705   141	I
ŀ	2400	Ø1500 X 1 Nos	2820	2820	25 EACH	50 EACH	150 X 1 NO	125 X 2 NOS	SIZES	0   1410	_
		Nos.						)S.	3S	1500	ľ

Base Frame

NOT TO SCALE / DO NOT SCALE DRAWING	JOB NO.:-
G.A OF DRG. OF COOLING TOWER MODEL NO. 6150 SERIES - DFC 60	TOWER MODEL NO. 6150 °C 60
COMPANY: Delta Cooling Towers P. Ltd Delhi	rs P. Ltd
(PH - 011-27495801/02/03) EMAIL- mail@delta.cool	mail@delta.cool
:ELIS	

DesignOnContract.com

REV: 12/2017