

Side View						5880 P
WITHOUT BOLT OF MKD - "S" (QTY- 9 NO.)	DETAIL—2  ELEVATION OF PILI	D 00	ELEVATION OF PILLER WITHOUT BOLT OF MKD - "R"  ALL PERIPHERAL ISA (ANGLES) SHALL BE (QTY- 16 NOS.)	DETAIL-X	100	10 mm. BOLES AT THE DISTANCE OF STATE DISTANCE OF STATE DISTANCE OF STATE PROPERTY BASE TRANS SHALL BE PROVIDED BY PRIFE ASSET.

BOLT / TOR 12mmX150mm LONG.

- Cooling tower will be assembled on isa-50x50x6 frame fixed on RCC pillar the frame is under purchasers scope unless otherwise stated.

- RCC basin and RCC pillers 250x250x700 ht. And Ø12 x 150 long bolts/tor are under purchaser scope.
- Location of outlet connection will be as per the site requirement.
- Ø12x150 long bolts/tor shall be grouted in the centre of outer columns as shown in the drawing.
- All pictures shown are for illustration purpose only and may differ from the actual cooling tower model.

515

490

1545 Z

1470 0

2400

DESCRIPTION INLET PIPE CONNECTION OUTLET PIPE CONNECTION DRAIN & OVERFLOW CONNECTION	MARK A B	SIZES 150 X 4 NOS. 200 X 2 NOS. 65 EACH
DRAIN & OVERFLOW CONNECTION	С	65 EACH
MAKEUP AND QUICKFILL CONNECTION	D	40 EACH
LENGTH OF COOLING TOWER	E	6180
WIDTH OF COOLING TOWER	F	5880
FAN DIA AND NOS.	P	Ø2400 X 2 Nos.
OPERATING WEIGHT (KG.)		11300

Delhi  Delhi (PH - 011-27495801/02/03) EMAIL- mail@delta.cool	
Delhi	0
Delta Cooling Towers P. Ltd	COMPANY:
G.A OF DRG. OF COOLING TOWER MODEL NO. 6750 SERIES - DFC 60	mua. G
NOT TO SCALE / DO NOT SCALE DRAWING JOB NO.:	NOT TO SCALE

DesignOnContract.com

REV: 1/2019