


ELEVATION OF PILLER WITHOUT BOLT OF MKD - "R" (QTY- 16 NOS.)

700

10 mm. HOLES AT THE DISTANCE OF 125mm. ON THE PERIPHERAL OF ISA OF THE BASE FRAME SHALL BE PROVIDED BY PURCHASER.

BOLT/TOR 12mmX150mm LONG.







700

ELEVATION OF PILLER WITHOUT BOLT OF MKD - "S" (QTY- 9 NO.)

- All dimensions are in milimeters.
- Cooling tower will be assembled on ISA-50x50x6 frame fixed on RCC pillar the frame is under purchasers scope unless othervise stated.
- Makeup and quickfill connection shall be provided with thread connections as per is-544-1955.

- RCC basin and RCC pillers 250x250x700 ht. And Ø12 x 150 long bolts/tor are under purchaser scope. 10 mm hole at the distance of 125mm on the peripheral of ISA of the base frame shall be provided by purchaser.
- Location of outlet connection will be as per the site requirement.
- 6480 6730 M 565 540 1695 Z 1620 0 2700

OPERATING WEIGHT (KG.)	FAN DIA AND NOS.	WIDTH OF COOLING TOWER	LENGTH OF COOLING TOWER	MAKEUP AND QUICKFILL CONNECTION	DRAIN & OVERFLOW CONNECTION	OUTLET PIPE CONNECTION	INLET PIPE CONNECTION	DESCRIPTION
	P	Ŧ	E	D	င	В	Α	MARK
13800	Ø2700 X 2 Nos.	6480	6780	40 X 1 NO.	65 X 1 NO.	200 X 2 NOS.	150 X 4 NOS.	SIZES

NOT TO SCALE / DO NOT SCALE DRAWING	JOB NO.:-
G.A OF DRG. OF COOLING TOWER MODEL NO. 6900 SERIES - DFC 60	TOWER MODEL NO. 6900 PC 60
COMPANY: Delta Cooling Towers P. Ltd	ars P. Ltd

nOnContract.com	(PH - 011-27495801/02/03) EMAIL- mail@delta.cool	Delta Cooling Towers P. Ltd
REV :- 12/2017	viAIL- mail@delta.cool	owers P. Ltd

Design